For a complete library of rotameter calibration data, visit:
http://www.mathesongas.com/gas-handling/rotameter-FAQ

MATHESON
ask. . .The Gas Professionals™

MATHESON
166 Keystone Drive
Montgomeryville, PA 18936
+1 (800) 828-4313
www.mathesongas.com

UNITS : SLPM SILANE
TUBE NUMBER : 604 (E700)
SERIAL NUMBER : TYPICAL
FLOAT MATERIAL: 316 ST. STL.

DATE : 10-01-67
STD CONDITIONS : 1 ATMOS. &70 DEG F
GAS TEMPERATURE : 70 DEG F
PRESSURE IN TUBE : 0 PSIG

E703SILA.DAT

SCALE READING	FLOW RATE	SCALE READING	FLOW RATE	SCALE READING	FLOW RATE	SCALE READING	FLOW RATE
150.0	16.50	110.0	12.17	70.0	7.97	30.0	3.73
149.0	16.39	109.0	12.06	69.0	7.87	29.0	3.62
148.0	16.28	108.0	11.95	68.0	7.76	28.0	3.52
147.0	16.17	107.0	11.85	67.0	7.66	27.0	3.41
146.0	16.06	106.0	11.74	66.0	7.55	26.0	3.30
145.0	15.94	105.0	11.64	65.0	7.45	25.0	3.19
144.0	15.83	104.0	11.53	64.0	7.34	24.0	3.08
143.0	15.72	103.0	11.43	63.0	7.24	23.0	2.97
142.0	15.61	102.0	11.32	62.0	7.13	22.0	2.86
141.0	15.50	101.0	11.22	61.0	7.03	21.0	2.76
140.0	15.39	100.0	11.11	60.0	6.92	20.0	2.65
139.0	15.28	99.0	11.01	59.0	6.82	19.0	2.54
138.0	15.17	98.0	10.90	58.0	6.71	18.0	2.43
137.0	15.06	97.0	10.80	57.0	6.61	17.0	2.32
136.0	14.95	96.0	10.69	56.0	6.50	16.0	2.21
135.0	14.84	95.0	10.59	55.0	6.40	15.0	2.10
134.0	14.74	94.0	10.48	54.0	6.29	14.0	1.99
133.0	14.63	93.0	10.38	53.0	6.19	13.0	1.88
132.0	14.52	92.0	10.27	52.0	6.08	12.0	1.77
131.0	14.41	91.0	10.17	51.0	5.97	11.0	1.66
130.0	14.30	90.0	10.06	50.0	5.87	10.0	1.55
129.0	14.19	89.0	9.96	49.0	5.76	9.0	1.44
128.0	14.09	88.0	9.86	48.0	5.66	8.0	1.33
127.0	13.98	87.0	9.75	47.0	5.55	7.0	1.22
126.0	13.87	86.0	9.65	46.0	5.44	6.0	1.10
125.0	13.76	85.0	9.54	45.0	5.34	5.0	0.99
124.0	13.66	84.0	9.44	44.0	5.23		
123.0	13.55	83.0	9.33	43.0	5.13		
122.0	13.44	82.0	9.23	42.0	5.02		
121.0	13.33	81.0	9.12	41.0	4.91		
120.0	13.23	80.0	9.02	40.0	4.81		
119.0	13.12	79.0	8.91	39.0	4.70		
118.0	13.01	78.0	8.81	38.0	4.59		
117.0	12.91	77.0	8.71	37.0	4.48		
116.0	12.80	76.0	8.60	36.0	4.38		
115.0	12.69	75.0	8.50	35.0	4.27		
114.0	12.59	74.0	8.39	34.0	4.16		
113.0	12.48	73.0	8.29	33.0	4.06		
112.0	12.38	72.0	8.18	32.0	3.95		
111.0	12.27	71.0	8.08	31.0	3.84		