



# Correlated Flow Table

Fluid Name Carbon Oxysulfide

Tube Size 610A

Density (grams/ml) 0.00252

Float Type Glass

Viscosity (cp) 0.01222

Serial No.

**TYPICAL**

Date 08/11/1993

Measured & flowing at 1.00 atm and 70 °F

SCALE DIVISION	FLOW RATE ML/MIN	SCALE DIVISION	FLOW RATE ML/MIN	SCALE DIVISION	FLOW RATE ML/MIN	SCALE DIVISION	FLOW RATE ML/MIN
1	0.415	26	14.6	51	41.1	76	73.4
2	0.561	27	15.5	52	42.2	77	74.7
3	0.734	28	16.4	53	43.4	78	76.1
4	0.936	29	17.3	54	44.5	79	77.5
5	1.17	30	18.3	55	45.7	80	78.9
6	1.43	31	19.3	56	46.9	81	80.3
7	1.73	32	20.3	57	48.1	82	81.7
8	2.06	33	21.3	58	49.3	83	83.1
9	2.42	34	22.3	59	50.6	84	84.5
10	2.82	35	23.4	60	51.9	85	85.9
11	3.26	36	24.4	61	53.2	86	87.3
12	3.73	37	25.5	62	54.5	87	88.7
13	4.25	38	26.6	63	55.8	88	90.1
14	4.80	39	27.7	64	57.1	89	91.5
15	5.45	40	28.7	65	58.4	90	92.9
16	6.20	41	29.8	66	59.8	91	94.2
17	6.98	42	30.9	67	61.1	92	95.6
18	7.77	43	32.0	68	62.4	93	97.0
19	8.58	44	33.2	69	63.8	94	98.4
20	9.40	45	34.3	70	65.1	95	99.7
21	10.2	46	35.4	71	66.5	96	101
22	11.1	47	36.5	72	67.9	97	102
23	11.9	48	37.6	73	69.2	98	104
24	12.8	49	38.8	74	70.6	99	105
25	13.7	50	39.9	75	72.0	100	106